

SDL1X

High-End Digital Level
0.2mm Standard Deviation for 1km Double-run Leveling

Ultimate Benchmark

The SDL1X is designed to achieve the highest precision and productivity in leveling and height measurement applications. From Intelligent Auto Focus to wireless operation, a number of innovative technologies are implemented for unmatched reliability while eliminating error factors during measurement. The SDL1X sets the ultimate benchmark for the precision digital levels.



■ Saving Measurement Time by up to 40%

- The combination of advanced "Auto Focus" and "View Finder" dramatically increases measurement speed.
- Measuring time – from sighting staff to completion of data storage – can be reduced by up to 40% compared to manual focus digital levels.

■ Seamless Switching Between Auto Focus and Manual

- No need to switch the focusing mode.
- Trigger key operation automatically starts Auto Focus.
- Manual focusing is possible at any time by rotating the focusing knob that supersedes the Auto Focus.

■ View Finder for Quick Sighting

- Innovative View Finder provides fast, easy and accurate sighting to the staff.
- In combination with Auto Focus, the SDL1X drastically reduces eye fatigue.

Eight innovative features never before available in the industry:*

1. 0.2mm precision (ISO17123-2)
2. Auto Focus for high-end digital level
3. View Finder for quick sighting
4. Remote Trigger for wireless operation
5. Dual-axis Tilt Sensor that ensures precision
6. SD card slot for data storage
7. 100m (320ft.) *Bluetooth*[®] wireless communication
8. BIS30A staff with ± 0.1 ppm/ $^{\circ}$ C linear expansion coefficient

* As of September 1, 2011

When Precision Has Top Priority, and Measurement Speed Also Matters, SDL1X is the Ideal Digital Level that Fully Satisfies Both Demands



Intelligent Auto Focus

- The SDL1X automatically focuses exclusively on the RAB-Code staff.
- This technology completely eliminates false focusing on undesirable objects, enhancing measurement efficiency and reliability.
- Furthermore, Auto Focus eliminates the incomplete focusing that often causes inaccurate measurement with digital levels.

Remote Trigger

- The wireless Remote Trigger DLC1 prevents accidental jolts from touching the instrument.



DLC1

Dual-axis Tilt Sensor

- The liquid dual-axis tilt sensor alerts the users by LCD display and beeps when instrument tilt exceeds $\pm 8.5'$, disabling measurement to avoid misreading.
- The LCD graphic circular level facilitates instrument setup.

Measurement and Recording Programs

- Onboard software supports height difference measurement and data recording in the following procedures:

BF, BFFB, BBFF, BFBF, aBF, aBFFB, aFBBF

(B: Backsight, F: Foresight, a: alternating)

- Measurement tolerance can be set in each route for on-site accuracy checks.

Up-to-date Data Memory and Interface

- 10,000-point internal memory.
- USB port and SD card slot for improved usability.

100m (320ft.) Bluetooth Wireless Modem (Optional)

- License-free Bluetooth technology enables wireless operation via various devices such as a data collector.

New Super-Invar Staff for 0.2mm Precision

- The SDL1X achieves the highest in precision when combined with the New Super-Invar RAB-Code Staff BIS30A that boasts the industry's lowest linear expansion coefficient $\pm 0.1\text{ppm}/^\circ\text{C}$.
- Ideal for first-order leveling as well as sub-millimeter height and subsidence measurement applications.



BIS30A

SDL1X Standard

A simple function model SDL1X Standard is also available. For details, please see the specifications.



SDL1X Standard

RAB-Code Staff

Material	Model	Length	Linear expansion coefficient
New Super-Invar	BIS30A	3m (9.84 ft.)	$\pm 0.1\text{ppm}/^\circ\text{C}$
	BIS20	2m (6.56 ft.)	1ppm/ $^\circ\text{C}$
	BIS30	3m (9.84 ft.)	1ppm/ $^\circ\text{C}$
Material	Model	Length	Reverse side graduation
Fiberglass	BGS40	4m (13.12 ft.)	Metric
	BGS50	5m (16.40 ft.)	Metric
	BGS50G3	5m (16.40 ft.)	feet / 10th / 100th

SDL1X Specifications

Model		Advanced	Standard
Height accuracy (ISO 17123-2) ¹	Electronic	0.2mm (0.008in.) ² with BIS30A staff 0.3mm (0.012in.) with BIS20/30 staffs 1.0mm (0.04in.) with BGS staffs	0.3mm (0.012in.) with BIS20/30(A) staffs 1.0mm (0.04in.) with BGS staffs
	Visual	1.0mm (0.04in.)	
Distance accuracy (D: measuring distance)	Electronic	< $\pm 10\text{mm}$ (< $\pm 0.4\text{in.}$): up to 10m (33ft.) < $\pm 0.1\%$ x D: to 50m (to 164ft.) < $\pm 0.2\%$ x D: to 100m (to 328ft.)	
	C & R correction	K=0.142 / 0.20 / none, selectable	
	Measuring range	Electronic	1.6 to 100m (5.3 to 328ft.)
Measuring mode	Visual	from 1.5m (5.0ft.)	
	Measuring mode	Single / Repeat / Average / Rapid-repeat	
Display resolution (selectable in all modes)	Height	0.00001 / 0.0001 / 0.001m (0.0001 / 0.001 / 0.01ft.)	
	Distance	0.001 / 0.01 / 0.1m (0.01 / 0.1 / 1ft.)	
Measuring time	Single/Repeat	< 2.5s	
	Average	< 2.5s x [number of measurements]	
	Rapid-repeat	< 1s	
Auto Focus	Method	Distance and Contrast measurement (Passive)	-
	Range	1.6 to 100m (5.3 to 328ft.)	-
	AF/MF modes	Automatic conversion	-
Telescope	Objective aperture: 45mm (1.8in.) Magnification: 32x, Resolving power: 3" Minimum focus: 1.5m (5ft.), Field of view: 1 $^\circ$ 20'		
View Finder	Magnification: 4.5x, Field of view: 3 $^\circ$		
Compensator	Type	Pendulum compensator with magnetic damping system	
	Working range	$\pm 12'$	
	Setting accuracy	$\pm 0.3''$	
Tilt warning	Sensor	Dual-axis liquid tilt sensor	
	Functions	Graphic display, Beep tones, Disabling measurement at $\pm 8.5'$ tilt (On/Off selectable)	
Display	LCD graphic display with LED backlight		
Keyboard	Alphanumeric, 27 keys with backlight		
DLC1 remote trigger (Standard model :optional)	Infrared, 3 keys (Trigger, ESC, Enter)		
Data storage	Internal memory	10,000 points	
	External memory	SD card (max.2GB), USB flash memory (max.4GB)	
Interface	RS-232C	Baud rate 1,200 to 57,600bps	
	USB	USB 1.1 Host Type A	
Bluetooth wireless modem (optional)	Ver. 2.0, Class 1, Range: 100m (328ft.)		
Sensitivity of levels	Circular level	8'/2mm	
	LCD graphic level	$\pm 12'$ /inner circle, $\pm 24'$ /outer circle	
Horizontal circle Graduation	1 $^\circ$ (1gon) Estimation: 0.1 $^\circ$ (0.1gon)		
Dust and water protection	IP54 (IEC60529:2001)		
Operating temperature	-20 to +50 $^\circ\text{C}$ (-4 to 122 $^\circ\text{F}$)		
Size	W226 x D260 x H200mm (W8.9 x D10.2 x H7.9in.)		
Weight with battery	3.5kg (7.7 lb.)		3.4kg (7.5 lb.)
	Power supply	Input voltage	7.2V DC (nominal)
Standard battery	BDC72 (Rechargeable Li-ion)		
	Operating time (at 20 $^\circ\text{C}$ (68 $^\circ\text{F}$))	Approx. 12 hours w/o Auto Focus	Approx. 14 hours
		Approx. 9 hours w/ Auto Focus	
Battery level display	4 levels and low level message		
Auto power cut-off	30 minutes after operation / none, selectable		

¹ Standard deviation for 1km double-run leveling.

² Conditions for the highest accuracy: Low level of atmospheric turbulence, stable ambient temperature, no direct sunlight on instrument and staff.

Standard Accessories

- BDC72 rechargeable battery • CDC77 quick charger with EDC113A/113B/113C power cable
- DLC1 Remote Trigger* • Tool kit • Operator's manual • Carrying case

*Optional Accessory for standard model

Optional Accessories

- DE28 diagonal eyepiece (32x) • DE29 diagonal eyepiece (44x) • DOC129 interface cable



TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan
Phone: (+81)3-3558-2993 Fax: (+81)3-3960-4214
www.topcon.co.jp

- Specifications may vary by region and are subject to change without notice.

- Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license.

- Other trademarks and trade names are those of their respective owners.

Your Local Authorized Dealer is:

C-49, Basement, Sector -10, Noida-201301 (UP) India

Mob: +91 9312403335, Tel: 0120 - 4263386

Email: delsales@paragoninstruments.com

H.O.: 9760091791, 9760091793

www.paragoninstruments.com